


Cushion caster for towing SKY-2 Type

# Excellent shock and vibration absorbing performance!



Shock relieving "Cushioning performance"

Lightly moveable "Starting performance"

Realize long service life "Durability performance"

No.1 ability for towing,  
YUEI CASTER

## SKY-2Type

**Light**

**Quiet**

**Strong**

**1**


### Verification of cushion performance

#### Absorbing shock by built-in spring

"Shock absorbing spring" reduces the impact transmitted from the unevenness (roughness) of the road surface, to about 1/5 of the conventional one (relative to our conventional products) and suppresses damage to the carriage.

#### Impact acceleration test

load	[daN] ([kgf])	50.00 (51.00)	100.00 (102.00)	150.00 (153.00)	200.00 (204.00)
<b>SKY-2S200WF (AR)</b>					
Max (Upward)		27.54	6.75	2.97	2.80
Min (Downward)		-16.15	-9.63	-3.85	-3.16
<b>WFJ-200 (AR)</b>					
Max (Upward)		71.83	19.59	12.76	20.51
Min (Downward)		-25.81	-11.95	-11.77	-13.60




**2**

### Turnability test

#### With light mobility, outstanding operability


By increasing the strength of the rotation part, the starting load is reduced by about 30% compared to conventional products (compared to our conventional products). Improved the initial operation that feels the heaviest when carrying and achieved smooth turning performance when changing direction.

Reduce less than  
**30% shock**  
※Compared with equivalent



#### Turn ability test result



load	[daN] ([kgf])	25.00 (25.50)	50.00 (51.00)	75.00 (76.50)	100.00 (102.00)
<b>SKY-2S200WF (AR)</b>					
Rotation Mobility	[daN] ([kgf])	3.89 (3.97)	6.15 (6.27)	8.84 (9.02)	10.03 (10.23)
<b>SKY-1S200WF (AR)</b>					
Rotation Mobility	[daN] ([kgf])	5.89 (5.97)	8.49 (8.66)	10.78 (11.00)	12.90 (13.16)



# Quiet & Strong

## New designed structure of bearing (turning parts)

New design of bearing structure improved holding power of steel ball. Aiming to dramatically improve turnability and also reduce rolling contact fatigue life. Steel ball scratching on the raceway isn't happened because turnability is stabilized. As a result, smooth running performance lasts long.



## Aluminum die-cast wheel excellent in rotation accuracy

Adopted self-developed aluminum wheels to reduce the side shift. Vibration of the wheel is greatly reduced, and noise is also reduced.

## Shock Absorbing Spring


By the built-in "Shock Absorbing Spring", load and wearing to wheel is reduced and realized long life. Depending on the usage environment but, the wear is reduced to 50% to 25% compared to the conventional wheel without spring.

2 springs available from usage

### Shock absorbing range of spring

Symbol	Spring color	
-1	Blue	225lbs
-2	Red	450lbs

We have 2 springs lineup to deal with various load weight. You are possible to choose suitable spring from your goods weight.



Product Name	Wheel	Wheel dimension D(inch)	Wheel width W(inch)	Mounting height H(inch)	Mounting base A			Mounting base B			Offset E(inch)	Turning radius R(inch)	Standard load [lbs]
					Mounting base (inch)	Mounting dimension XX(Y'X'Y'Y' inch)	Hole dimension (inch)	Mounting base (inch)	Mounting dimension XX(Y'X'Y'Y' inch)	Hole dimension (inch)			
SKY-2S150WF (AR)	Abrasion Resistant Rubber (including B)	6	1.57	7.59~7.20	6.25×4.48	5.23×3.38 (4.92×2.44)	0.53	4.72×4.72	3.70×3.70 (3.42×3.42)	0.43	1.96	4.96	-1 225
SKY-2R150WF (AR)		6	1.57	7.59~7.20			0.53	5.39×3.66	4.40×1.96 (3.93×2.20)	0.43	1.96	—	-2 450
SKY-2S200WF (AR)		8	1.69	9.68~9.29			0.53	5.66×5.66	4.72×4.72 (4.13×4.13)	0.45	2.55	6.53	-1 225
SKY-2R200WF (AR)		8	1.69	9.68~9.29			0.53	7.08×4.33	4.40×2.48 (5.51×1.96)	0.45	2.55	—	-2 450
SKY-2S150WF (Gr)	Rubber (including B)(Green)	6	1.57	7.59~7.20	6.25×4.48	5.23×3.38 (4.92×2.44)	0.53	4.72×4.72	3.70×3.70 (3.42×3.42)	0.43	1.96	4.96	-1 225
SKY-2R150WF (Gr)		6	1.57	7.59~7.20			0.53	5.39×3.66	4.40×1.96 (3.93×2.20)	0.43	1.96	—	-2 450
SKY-2S200WF (Gr)		8	1.69	9.68~9.29			0.53	5.66×5.66	4.72×4.72 (4.13×4.13)	0.45	2.55	6.53	-1 225
SKY-2R200WF (Gr)		8	1.69	9.68~9.29			0.53	7.08×4.33	4.40×2.48 (5.51×1.96)	0.45	2.55	—	-2 450
SKY-2S150AW	Rubber (including B)	6	1.65	7.59~7.20	6.25×4.48	5.23×3.38 (4.92×2.44)	0.53	4.72×4.72	3.70×3.70 (3.42×3.42)	0.43	1.96	4.96	-1 225
SKY-2R150AW		6	1.65	7.59~7.20			0.53	5.39×3.66	4.40×1.96 (3.93×2.20)	0.43	1.96	—	-2 450
SKY-2S200AW		8	1.77	9.68~9.29			0.53	5.66×5.66	4.72×4.72 (4.13×4.13)	0.45	2.55	6.53	-1 225
SKY-2R200AW		8	1.77	9.68~9.29			0.53	7.08×4.33	4.40×2.48 (5.51×1.96)	0.45	2.55	—	-2 450
SKY-2S150AW (AR) Gr	Abrasion Resistant Rubber (including B)(Green)	6	1.65	7.59~7.20	6.25×4.48	5.23×3.38 (4.92×2.44)	0.53	4.72×4.72	3.70×3.70 (3.42×3.42)	0.43	1.96	4.96	-1 225
SKY-2R150AW (AR) Gr		6	1.65	7.59~7.20			0.53	5.39×3.66	4.40×1.96 (3.93×2.20)	0.43	1.96	—	-2 450
SKY-2S200AW (AR) Gr		8	1.77	9.68~9.29			0.53	5.66×5.66	4.72×4.72 (4.13×4.13)	0.45	2.55	6.53	-1 225
SKY-2R200AW (AR) Gr		8	1.77	9.68~9.29			0.53	7.08×4.33	4.40×2.48 (5.51×1.96)	0.45	2.55	—	-2 450
SKY-2S150UWF	Urethane (including B)	6	1.49	7.59~7.20	6.25×4.48	5.23×3.38 (4.92×2.44)	0.53	4.72×4.72	3.70×3.70 (3.42×3.42)	0.43	1.96	4.96	-1 225
SKY-2R150UWF		6	1.49	7.59~7.20			0.53	5.39×3.66	4.40×1.96 (3.93×2.20)	0.43	1.96	—	-2 450
SKY-2S200UWF		8	1.65	9.68~9.29			0.53	5.66×5.66	4.72×4.72 (4.13×4.13)	0.45	2.55	6.53	-1 225
SKY-2R200UWF		8	1.65	9.68~9.29			0.53	7.08×4.33	4.40×2.48 (5.51×1.96)	0.45	2.55	—	-2 450
SKY-2S150UWF/INJ	Urethane (including B)	6	1.49	7.59~7.20	6.25×4.48	5.23×3.38 (4.92×2.44)	0.53	4.72×4.72	3.70×3.70 (3.42×3.42)	0.43	1.96	4.96	-1 225
SKY-2R150UWF/INJ		6	1.49	7.59~7.20			0.53	5.39×3.66	4.40×1.96 (3.93×2.20)	0.43	1.96	—	-2 450
SKY-2S200UWF/INJ		8	1.65	9.68~9.29			0.53	5.66×5.66	4.72×4.72 (4.13×4.13)	0.45	2.55	6.53	-1 225
SKY-2R200UWF/INJ		8	1.65	9.68~9.29			0.53	7.08×4.33	4.40×2.48 (5.51×1.96)	0.45	2.55	—	-2 450

■ Description of product number SKY- 2S 150 AW - A - 1

Bracket type Wheel dimension Wheel Mounting dimension Spring type

## YUEI Co., Ltd.

■ TOKYO Branch	Zip code: 101-0021 2nd. Floor, Prostech Akihabara, 6-13-10, Sotokanda, Chiyoda-ku, Tokyo +81-3-5816-1155 (proxy)
■ CHUBU Branch	Zip code: 486-0824 58 Warizuka-cho, Kasugai city, Aichi +81-568-86-3066 (proxy)
■ OSAKA Branch	Zip code: 540-0025 2-1-10 Tokui-cho, Chuo-ku, Osakacity, Osaka +81-6-4791-3586
■ HIROSHIMA Branch	Zip code: 733-0002 No.102, Shinko Building, 2-5-18, Kusunoki-cho, Nishi-ku, Hiroshima city, Hiroshima +81-82-509-2105
■ Fukuoka Branch	Zip code: 812-0023 3F, NS Naraya building, 11-6, Naraya-machi, Hakata-ku, Fukuoka city Fukuoka +81-92-261-5607
■ Overseas Sales	Zip code: 540-0025 2-1-10 Tokui-cho, Chuo-ku, Osakacity, Osaka +81-6-4791-3585

You can download the drawing via HP. [www.yueicaster.co.jp](http://www.yueicaster.co.jp)

● The content of this flyer is a thing of Dec-2023 current. ● The color of the product may be a little different than real thing.  
● Please note that appearance and specification may be changed for improving the product.